

## 156-835<sup>Q&As</sup>

Check Point Certified Maestro Expert

### Pass CheckPoint 156-835 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/156-835.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by CheckPoint  
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



## QUESTION 1

How many orchestrators may Dual-Site include\?\?

- A. 2 or 4
- B. 2
- C. Only 4
- D. 1

Correct Answer: A

---

## QUESTION 2

What is an uplink interface used for?

- A. To connect in between Orchestrators
- B. To connect appliances to customer\?\s infrastructure
- C. To connect Orchestrators to customer\?\s infrastructure
- D. D.To connect in between appliances

Correct Answer: B

---

## QUESTION 3

What cannot be learned from the output of Ildpctl?

- A. Distribution mode
- B. Orchestrator\?\s IP
- C. Serial number of Appliance
- D. Appliance model

Correct Answer: A

---

## QUESTION 4

There is a Security group of 10 Appliances and all of them are up and running. How many Appliances within a Security Group keep the same connection in its connection table in case of NAT?

- A. Between 2 and 4

B. 3

C. All 10

D. 2

Correct Answer: A

---

## QUESTION 5

Complete the sentence: When using a Break-out cable...

A. All tails of the break-out cable must represent the same type of ports

B. All tails of the break-out cable must represent uplinks

C. Each tail of the break-out cable represent an independent port

D. All tails of the break-out cable must represent downlinks

Correct Answer: C

[156-835 Practice Test](#)

[156-835 Exam Questions](#)

[156-835 Braindumps](#)